

## 3 Strand Nylon Anchor Rope

Pre-Spliced For Anchor Windlass

HIGH TORQUE HIGH SPEED

### Features:

Nylon will stretch by about 20% at 50% of its breakload, compared with 12% stretch for Polyester at equivalent loads. This high elongation makes 3 Strand Nylon a good choice for anchor warps, mooring warps and mooring risers.

Care should be taken when choosing 3 Strand Nylon ropes through, as Nylon is susceptible to external environmental factors such as salt water and UV.

Nylon will stretch by about 20% at 50% of its breakload, compared with 12% stretch for Polyester at equivalent loads.



Diameter (mm)	6	8	10	12	14	16	18	20	24	28	32
Weight (Kg/100m)	2.3	4	6.2	8.9	12.2	15.8	20	24.5	35.5	48.5	63
Av. Breakload (Kg)	860	1540	2400	3560	4850	5520	6900	8630	12400	16900	22080
Min. Breakload (Kg)	808	1,407	2,161	3,068	4,077	5,291	6,555	8,073	11,417	15,189	19,572
Colours	White / Blue / Black / Green										
Lengths (m)	70 80 95 100 150 200										

### BENEFITS:

High elongation High strength Very easily spliced

### AVAILABLE DIAMETERS:

6mm 8mm 10mm 12mm 14mm 16mm 18mm 20mm 24mm 28mm 32mm



### 5 Year Warranty

All Hiniu Marine boat equipment come with a 5 Year Warranty. All our material is premium marine grade environment. Quality machining and hand polishing finish.